



Notes,

1.To maximize output force and life of linear actuators, radial load on lead screws should be avoided or be kept at a minimum.

CUSTOMER						NOTICE TO PERSONS RECEIVING THIS DRAWING THIS DRAWING IS ONLY CONDITIONALY ISSUED, AND FOR THE SOLE PURPOSE OF INFORMING LICENSEES AND ASSOCIATE CONTRACTORS OF DINGS' MOTION, AND VENDORS THERETO AND CUSTOMERS THEREOF, RECEIPT OR POCESSION THEREOF DOES NOT CONFER TO TRANSFER ANY RIGHT IN THE SUBJECT MATTER OF THE DRAWING. THE DESIGN, CONSTRUCTION, TECHNICAL INFORMATION AND ALL OTHER SUBJECT MATTER SHOWN IN THIS DRAWING ARE AND REMAIN, EXCEPT AS MAY BE OTHERWISE INDICATED BY WRITTEN ONTICE HEREON, THE EXCLUSIVE PROPERTY OF SAID CORPORATION. THIS DRAWING MAY BE REPRODUCED ONLY BY LICENSEES													
WIRING CHART	EXCITATION SEQUENCE					AND ASSOCIATE CONTRACTORS OF SAID CORPORATION AND ONLY FOR LICENSES MANUFACTURE, AND BY VENDORS MANUFACTURING FOR SAID CORPORATION AND ONLY FOR LICENSES AND ASSOCIATECONTRACTORS.													
A+ M	CW	$\stackrel{-}{\longrightarrow}$				UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE AS BELOW PER ISO2768-ck.				DRAWN	Alice	DATE	2020/11/12	DINCS					
	Red A+	+ -				LINEAR ANGULAR				APPRVD	DATE				DII4G2				
	Red/wht A-	-		+		$0 \sim 3$ ±0.2 $0 \sim 10$ ±1.5°													
	Green B+		+		-	3~6	±0.5	10 ~50		L				SIZE	A3 SI	HEET	1 OF 1	-	
	Grn/wht B-		-		+					MODEL	8N22-100		<u> </u>			\dashv			
	CCW	\leftarrow				6~30 30~120	±0.8 ±1.5	50 ∼120 120 ∼400	±30′ ±15′					SCALE	1: 1	REV	00	-	