



Product Service

# Attestation of Conformity

No. N8A 077217 0035 Rev. 01

**Holder of Attestation:** **China Leadshine Technology Co.,Ltd.**  
15-20/F, Block B, Nanshan I Valley, No.3157, Shahe West Road  
Nanshan District  
518055 Shenzhen  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Electronic frequency converter  
(AC SERVO DRIVER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64105243007102

**Date,** 2025-11-04

  
( Kevin Liu )

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



# Attestation of Conformity

No. N8A 077217 0035 Rev. 01

**Model(s):**

**L8 series, EL8 series**

L8 P - (a) 1500 F (b) - (c)  
I II III IV V VI VII

**I Series designation**

L8: L8 series (Chinese series)

**II Communication ports**

P: Pulse and RS485

EC: EtherCAT

**III Industry code (not relevant to safety construction)**

(a): XXXXXXXXXXX

The model number may include a "XXXXXXXXXX",  
Where "XXXXXXXXXX" can be blank or combination  
of any alphanumeric and/or symbols that represents  
Industry

(blank): Standard model, not industry customized (default)

**IV Rated power**

1500: 1500W

(Input: 1PH or 3PH AC 200-240V 50/60Hz 10.1A/6.4A;  
output: 3PH AC 0-240V 0-500Hz 9.5A 1500W)

2000: 2000W

(Input: 1PH or 3PH AC 200-240V 50/60Hz 12.8A/8.0A;  
output: 3PH AC 0-240V 0-500Hz 12A 2000W)

**V Type**

(blank): Standard version (default)

F: Full function version (supports full loop and STO  
functions)

**VI Product code (not relevant to product construction)**

(b): The model number may include a "XXXXXXXXXX",  
Where "XXXXXXXXXX" can be blank or combination  
of any alphanumeric and/or symbols that represents  
product code.

**VII Customer code (not relevant to safety construction)**

(c): XXXXXXXXXXX

The model number may include a suffix  
"XXXXXXXXXX", Where "XXXXXXXXXX" can be  
blank or combination of any alphanumeric and/or  
symbols that represents customer identity.



Product Service

# Attestation of Conformity

No. N8A 077217 0035 Rev. 01

EL8 - RS 1500 F - (a) - (b)  
I II III IV V VI

**I Series designation**

EL8: EL8 series (Overseas series)

**II Communication ports**

RS: Pulse and Modbus

EC: EtherCAT

**III Rated power**

1500: 1500W

(Input: 1PH or 3PH AC 200-240V 50/60Hz 10.1A/6.4A;  
output: 3PH AC 0-240V 0-500Hz 9.5A 1500W)

2000: 2000W

(Input: 1PH or 3PH AC 200-240V 50/60Hz 12.8A/8.0A;  
output: 3PH AC 0-240V 0-500Hz 12A 2000W)

**IV Type**

(blank): Standard version (default)

F: Full function version (supports full loop and STO functions)

**V Product code (not relevant to product construction)**

(a): The model number may include a "XXXXXXXXXX",  
Where "XXXXXXXXXX" can be blank or combination  
of any alphanumeric and/or symbols that represents  
product code.

**VI Customer code (not relevant to safety construction)**

(b): XXXXXXXXXXX

The model number may include a suffix  
"XXXXXXXXXX", Where "XXXXXXXXXX" can be blank  
or combination of any alphanumeric and/or symbols  
that represents customer identity.

## Parameters:

Protection class:	I
Degree of pollution:	2
Overvoltage Category:	III
Construction:	Built-in

**Remark:**

- When installing the equipment, all requirements of the mentioned standard must be fulfilled and it should be suitably installed in closed electrical operation area, and fire/mechanical protection enclosure shall be provided.

- For safe operation, a suitable external circuit breaker or fuse must be employed before installation.

## Tested according to:

EN 61800-5-1:2007/A11:2021

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.