# MDrive® Plus MDI•14

NEMA 14 (35mm) CANopen integrated 1.8° 2-phase stepper motor & control electronics

# CE REACH IP20

### **PRODUCT OVERVIEW**

MDrive Plus CANopen products integrate 1.8° 2-phase stepper motor, motion controller, drive electronics and optional encoder. Products support CiA DS301 and DSP402 Device Profile for Drives and Motion Control.

Firmware is provided for setup and testing MDrive Plus CANopen products. CANopen Tester software and communication dongle (MD-CC500-000) are also available.

MDrive Plus products deliver reliable performance for new and existing motion control applications. Satisfying the requirements for a wide range of machine builders.

Simplify your machine design and reduce cabinet size by replacing multiple components with a single compact integrated motor. Fewer individual system components eliminates multiple potential failure points, and lowers risk of electrical noise by eliminating cabling between motor and drive.

These compact, powerful and cost effective motion control solutions deliver exceptional smoothness and performance that can reduce system cost, design and assembly time for a large range of 2-phase stepper motor applications.

## **FEATURES AND BENEFITS**

- Compact integrated microstepping drive, motion controller and NEMA 14 1.8° 2-phase stepper motor
- Advanced current control with automatic current reduction for exceptional performance and smoothness
- Single supply: +12 to +48 VDC
- 20 microstep resolutions up to 51,200 steps per rev including: Degrees, Metric, Arc Minutes
- IP20 protection rating
- Auxiliary logic power supply input
- 0 to 5 MHz step clock rate selectable in 0.59 Hz increments
- Up to eight I/O lines and one 10-bit selectable analog input
- Programmable motor run/hold current
- Available options include:
  - Encoder
  - Multiple motor stack lengths
  - Long life linear actuators
  - Rear control knob for manual positioning
- Single & triple motor stack lengths available
- Graphical user interface provided for quick and easy configuration and programming via optional MD-CC500-000 comm converter



Additional setup, quick reference information, and supporting documents are available for download from the Novanta IMS download website <a href="https://novantaims.com/dloads/">https://novantaims.com/dloads/</a>

Three-dimensional depictions of this product are available for download from <a href="https://novantaims.com/dloads/3d-product-models/">https://novantaims.com/dloads/3d-product-models/</a>





To select from the available features and build the LMD integrated stepper motor to fit your needs, use the Novanta IMS part number builder, available online at <a href="https://novantaims.com/resources/part-number-builders/">https://novantaims.com/resources/part-number-builders/</a>





# MDrive Plus MDI•14 CANopen

### **Motor Performance**

			MDrive 14	
Motor	Stack length	Single	Triple	
Holding toyour	oz-in	18 13 2.0 1.4 -sec <sup>2</sup> 0.000198	36	
Holding torque	N-cm	13	25	
Detent terrile	oz-in	2.0	4.4	
Detent torque	N-cm	1.4	3.1	
Dahay in autic	oz-in-sec <sup>2</sup>	0.000198	0.000801	
Rotor inertia	kg-cm <sup>2</sup>	18 13 2.0 1.4 0.000198 0.014 5.29	0.0566	
NA/a i aula be coma a be a un le aluriu ca un	OZ	5.29	12.8	
Weight (motor+driver)	g	150	380	

### **Motor Speed Torque**





Test conditions: 100% current with damper simulating load.

### Accessories

2

Description	Length feet (m)	Part Number
Communication Converter Electrically isolated, in-line converter pre-wired with mating connector to conveniently set/program communication parameters for a single MDrive Plus via a PC's USB port.		
Interface cable for all CANopen products. Requires mating connector adapter for DB9 connector. Requires power supply, not supplied.	12.0 (3.6)	MD-CC500-000
Prototype Development Cables Speed test/development with pre-wired mating connector with other cable end open.		
Mates to 16-pin locking wire crimp connector for I/O and power	10.0 (3.0)	PD16-1417-FL3
Mating Connector Kit Connectors for the assembly of cables. (Cable material not included). Sold in lots of 5. Manufacturer's crimp tool recommended for crimp connectors		
16-pin locking wire crimp connector for I/O and power	_	CK-10
Drive Protection Module Limits surge current and voltage to a safe level when DC input power to the MDrive Plus is switched on and off		
For all MDrive 14 CANopen products	_	DPM75

IMS-PO-MDIA14\_A.pdf