

## BRAKE FEATURES

|                     |                    | SKA DDR 090                 |       |
|---------------------|--------------------|-----------------------------|-------|
| Static Torque @20°C | Nm                 | 2                           | 4,5   |
| Moment of Inertia   | Kg cm <sup>2</sup> | 0,050                       | 0,220 |
| Rated Current       | A                  | 0,46                        | 0,5   |
| Input Power         | W                  | 11                          | 12    |
| Engaging Time       | ms                 | 6                           | 7     |
| Release Time        | ms                 | 25                          | 35    |
| Operating Voltage   |                    | 24 Vdc +6% - 10% Stabilized |       |

|                     |                    | SKA DDR 148                 |      |
|---------------------|--------------------|-----------------------------|------|
| Static Torque @20°C | Nm                 | 18                          | 36   |
| Moment of Inertia   | Kg cm <sup>2</sup> | 1,9                         | 6,21 |
| Rated Current       | A                  | 1                           | 1,08 |
| Input Power         | W                  | 24                          | 26   |
| Engaging Time       | ms                 | 10                          | 22   |
| Release Time        | ms                 | 50                          | 90   |
| Operating Voltage   |                    | 24 Vdc +6% - 10% Stabilized |      |

|                     |                    | SKA DDR 245 - 335 - 430     |  |
|---------------------|--------------------|-----------------------------|--|
| Static Torque @20°C | Nm                 | 72                          |  |
| Moment of Inertia   | Kg cm <sup>2</sup> | 15,3                        |  |
| Rated Current       | A                  | 1,66                        |  |
| Input Power         | W                  | 40                          |  |
| Engaging Time       | ms                 | 7                           |  |
| Release Time        | ms                 | 140                         |  |
| Operating Voltage   |                    | 24 Vdc +6% - 10% Stabilized |  |

SEE IT BEFORE IT HAPPENS