



WIRING MOTOR CONNECTIONS

POWER CONNECTION


Function	D0	D0 + Brake	C2	C3
U	PIN 1	PIN 1	PIN 1	PIN E
V	2	2	4	G
W	3	4	3	B
PE	4	5	2	D
BRAKE_24V	-	3	A	F
BRAKE_0V	-	6	B	A



[D0]




[D0 + Brake]



[C2]



[C3 for mod. TC-E 100 and 130]



[C3 for mod. TC-E 180]

WIRING MOTOR CONNECTIONS

E1 FEEDBACK CONNECTION

D0 connection


Function	PIN
A	1
A/	2
B	3
B/	4
Z	5
Z/	6
HALL U	7
HALL U/	8
HALL V	9
HALL V/	10
HALL W	11
HALL W/	12
+5V	13
0V	14
SHIELD	15

C2 connection


Function	PIN
HALL W	1
HALL U	2
0V	3
+5 Vdc	4
Ch /A	5
Ch A	6
Ch /z	7
Ch z	8
HALL V	9
SHIELD	10
Ch /B	11
Ch B	12
HALL /W	13
HALL /V	14
HALL /U	15

C3 connection


Function	PIN
A	A
A/	B
B	C
B/	D
Z	E
Z/	F
HALL U	G
HALL U/	H
HALL V	J
HALL /V	K
HALL W	L
HALL /W	M
+5 Vdc	N
GND	P
SHIELD	R



[D0]



[C2]



[C3]

WIRING MOTOR CONNECTIONS


A1 FEEDBACK CONNECTION

D0 connection


C2 connection

C3 connection


Function	PIN	Function	PIN	Function	PIN
DATA +	1	GND	3	8V/ Us	A
+ SIN	2	Us (+7Vdc ÷ +12Vdc)	4	+ SIN	B
REFSIN	3	REFSIN	5	REFSIN	C
DATA -	4	+ SIN	6	+ COS	D
+ COS	5	DATA -	7	REFCOS	E
REFCOS	6	DATA +	8	GND	F
8V/ Us	7	SHIELD	10	DATA -	G
GND	8	REFCOS	11	DATA -	H
SHIELD	9	+ COS	12	SHIELD	J



[D0]



[C2]



[C3]

A2 FEEDBACK CONNECTION


Function

D0 connection


C2 connection

C3 connection


Function	PIN	PIN	PIN
DATA +	1	6	A
DATA -	4	5	B
-	2	-	C
-	3	-	D
-	5	-	F
-	6	-	G
DC +5V (BATTERY +)	7	4	S
GND (BATTERY -)	8	3	R
SHIELD	9	10	L



[D0]



[C2]



[C3]

SEE IT BEFORE IT HAPPENS

**MOTOR
POWER**
COMPANY


CABLES SPECIFICATIONS

Dynamic laying cable E83517 – cRUus AWM STYLE 21223 certified

POWER CABLES for models TC-E 40-60-80 without holding brake for D0 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black 1	Lenght (mm)	Order code
4	FASE V	Black 2	3000	003108015156
7	FASE W	Black 3	5000	003108015157
8	PE	Yellow-Green	10000	003108015155


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 40-60-80 with holding brake for D0 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black 1	Lenght (mm)	Order code
2	FASE V	Black 2	3000	003108015159
4	FASE W	Black 3	5000	003108015160
5	PE	Yellow-Green	10000	003108015158
3	BRAKE 1	Brown		
6	BRAKE 2	White		


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 100 4A - 130 5A - 130 5B - 130 5C - 130 5D - 130 5E - 130 5F - 130 5G without holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
E	FASE U	White	Lenght (mm)	Order code
G	FASE V	Black	3000	003108015244
B	FASE W	Red	5000	003108015245
D	PE	Yellow-Green	10000	003108015246

Power free wire cable for FLEXI-PRO and general purpose



SEE IT BEFORE IT HAPPENS

**MOTOR
POWER**
COMPANY


CABLES SPECIFICATIONS

Dynamic laying cable E83517 – cRUus AWM STYLE 21223 certified

POWER CABLES for models TC-E 100 4A - 130 5A - 130 5B - 130 5C - 130 5D - 130 5E - 130 5F - 130 5G with holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
E	FASE U	White	Lenght (mm)	Order code
G	FASE V	Black	3000	003108015247
B	FASE W	Red	5000	003108015248
D	PE	Yellow-Green	10000	003108015249
F	BK +	Red		
A	BK -	Black		


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 100 4B - 130 5H without holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
E	FASE U	White	Lenght (mm)	Order code
G	FASE V	Black	1500	003108015164
B	FASE W	Red	3000	003108015165
D	PE	Yellow-Green	5000	003108015166
			10000	003108015228


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 100 4B - 130 5H with holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
E	FASE U	White	Lenght (mm)	Order code
G	FASE V	Black	3000	003108015168
B	FASE W	Red	5000	003108015169
D	PE	Yellow-Green	10000	003108015167
F	BK +	Red		
A	BK -	Black		

Power free wire cable for FLEXI-PRO and general purpose



SEE IT BEFORE IT HAPPENS

**MOTOR
POWER**
COMPANY

CABLES SPECIFICATIONS

Dynamic laying cable E83517 – cRUus AWM STYLE 21223 certified

POWER CABLES for models TC-E 180 6A - 180 6B - 180 6C - 180 6D without holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black 1	Lenght (mm)	Order code
4	FASE V	Black 2	3000	003108015177
7	FASE W	Black 3	5000	003108015178
8	PE	Yellow-Green	10000	003108015176


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 180 6A - 180 6B - 180 6C - 180 6D with holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
E	FASE U	White	Lenght (mm)	Order code
G	FASE V	Black	3000	003108015180
B	FASE W	Red	5000	003108015181
D	PE	Yellow-Green	10000	003108015179
F	BK +	Red		
A	BK -	Black		

Power free wire cable for FLEXI-PRO and general purpose



SEE IT BEFORE IT HAPPENS

**MOTOR
POWER**
COMPANY


CABLES SPECIFICATIONS

Dynamic laying cable E83517 – cRUus AWM STYLE 21223 certified

POWER CABLES for models TC-E 180 6E - 180 6F - 180 6G without holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black 1	Lenght (mm)	Order code
4	FASE V	Black 2	3000	003108015183
7	FASE W	Black 3	5000	003108015184
8	PE	Yellow-Green	10000	003108015182


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 180 6E - 180 6F - 180 6G with holding brake for C3 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
E	FASE U	White	Lenght (mm)	Order code
G	FASE V	Black	3000	003108015186
B	FASE W	Red	5000	003108015187
D	PE	Yellow-Green	10000	003108015185
F	BK +	Red		
A	BK -	Black		

Power free wire cable for FLEXI-PRO and general purpose



SEE IT BEFORE IT HAPPENS

**MOTOR
POWER**
COMPANY


CABLES SPECIFICATIONS

Dynamic laying cable E83517 – cЯUus AWM STYLE 21223 certified

POWER CABLES for models TC-E 60- 80 -100 4A - 130 5A - 130 5B - 130 5C - 130 5D - 130 5E - 130 5F - 130 5G without holding brake for C2 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black	Lenght (mm)	Order code
4	FASE V	Black	3000	003108015250
3	FASE W	Black	5000	003108015251
2	PE	Yellow-Green	10000	003108015252


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 60 - 80 - 100 4A - 130 5A - 130 5B - 130 5C - 130 5D - 130 5E - 130 5F - 130 5G with holding brake for C2 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black	Lenght (mm)	Order code
4	FASE V	Black	3000	003108015253
3	FASE W	Black	5000	003108015254
2	PE	Yellow-Green	10000	003108015255
A	BK +	Black		
B	BK -	White		


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 100 4B - 130 5H without holding brake for C2 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black	Lenght (mm)	Order code
4	FASE V	Black	3000	003108015192
3	FASE W	Red	5000	003108015193
2	PE	Black	10000	003108015191

Power free wire cable for FLEXI-PRO and general purpose




CABLES SPECIFICATIONS

Dynamic laying cable E83517 – cRUus AWM STYLE 21223 certified

POWER CABLES for models TC-E 100 4B - 130 5H with holding brake for C2connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black	Lenght (mm)	Order code
4	FASE V	Black	3000	003108015195
3	FASE W	Black	5000	003108015196
2	PE	Yellow-Green	10000	003108015194
A	BK +	Black		
B	BK -	White		


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 180 6A - 180 6B - 180 6C - 180 6D without holding brake for C2 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black	Lenght (mm)	Order code
4	FASE V	Black	3000	003108015204
3	FASE W	Black	5000	003108015205
2	PE	Yellow-Green	10000	003108015203


Power free wire cable for FLEXI-PRO and general purpose



POWER CABLES for models TC-E 180 6A - 180 6B - 180 6C - 180 6D with holding brake for C2 connection

PIN motor side	FUNCTION	Cable wire colour	For cable order	
1	FASE U	Black	Lenght (mm)	Order code
4	FASE V	Black	3000	003108015207
3	FASE W	Black	5000	003108015208
2	PE	Yellow-Green	10000	003108015206
A	BK +	Black		
B	BK -	White		

Power free wire cable for FLEXI-PRO and general purpose




CABLES SPECIFICATIONS

Dynamic laying cable E83517 cULus AWM STYLE 20233 and E83517 – cRUus AWM STYLE 20549 certified

SIGNAL CABLES for models TC-E 40-60-80 feedback A1 absolute multiturn encoder for D0 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
1	DATA +	1	Lenght (mm)	Order code
2	SIN +	9	3000	003108015210
3	SIN -	22	5000	003108015211
4	DATA -	14	10000	003108015209
5	COS +	10		
6	COS -	23		
7	8 VDC	18		
8	GND	24		
9	SHIELD	26		


Signal wired cable for FLEXI-PRO with absolute multiturn encoder



SIGNAL CABLES for models TC-E 40-60-80 feedback E1 incremental encoder for D0 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
1	A	1	Lenght (mm)	Order code
2	A/	14	3000	003108015219
3	B	2	5000	003108015220
4	B/	15	10000	003108015218
5	Z	3		
6	Z/	16		
7	HU	4		
8	HU/	NC		
9	HV	17		
10	HV/	NC		
11	HW	5		
12	HW/	NC		
13	5 VDC	11		
14	GND	24		
15	SHIELD	26		

Signal wired cable for FLEXI-PRO with incremental encoder




CABLES SPECIFICATIONS

Dynamic laying cable E83517 cULus AWM STYLE 20233 and E83517 – cRUus AWM STYLE 20549 certified

SIGNAL CABLES for models TC-E 40-60-80 feedback A2 20 bit absolute encoder for D0 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
1	DATA +	1	Lenght (mm)	Order code
4	DATA -	14	3000	003108015162
7	5 VDC	11	5000	003108015163
8	GND	24	10000	003108015161
9	SHIELD	26		


Signal wired cable for FLEXI-PRO with 20 bit absolute encoder



SIGNAL CABLES for models TC-E 100 - 130 - 180 feedback A1 absolute multiturn encoder for C3 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
A	8 VDC	18	Lenght (mm)	Order code
B	SIN +	9	3000	003108015213
C	SIN -	22	5000	003108015214
D	COS +	10	10000	003108015212
E	COS -	23		
F	GND	24		
G	DATA +	1		
H	DATA -	14		
J	SHIELD	26		

Signal wired cable for FLEXI-PRO with absolute multiturn encoder




CABLES SPECIFICATIONS

Dynamic laying cable E83517 cULus AWM STYLE 20233 and E83517 – cRUus AWM STYLE 20549 certified

SIGNAL CABLES for models TC-E 100 - 130 - 180 feedback E1 incremental encoder for C3 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
A	A	1	Lenght (mm)	Order code
B	A/	14	3000	003108015222
C	B	2	5000	003108015223
D	B/	15	10000	003108015221
E	Z	3		
F	Z/	16		
G	HU	4		
H	HU/	NC		
J	HV	17		
K	HV/	NC		
L	HW	5		
M	HW/	NC		
N	5 VDC	11		
P	GND	24		
Q	SHIELD	26		


Signal wired cable for FLEXI-PRO with incremental encoder



SIGNAL CABLES for models TC-E 100 - 130 - 180 feedback A2 20 bit absolute encoder for C3 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
A	DATA +	1	Lenght (mm)	Order code
B	DATA -	14	1500	003108015188
S	5 VDC	11	3000	003108015189
R	GND	24	5000	003108015190
L	SHIELD	26	10000	003108015227

Signal wired cable for FLEXI-PRO with 20 bit absolute encoder




CABLES SPECIFICATIONS

Dynamic laying cable E83517 cULus AWM STYLE 20233 and E83517 – cRUus AWM STYLE 20549 certified


SIGNAL CABLES for models TC-E 60 - 80 - 100 - 130 - 180 feedback A1 absolute multiturn encoder for C2 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
4	8 VDC	18	Lenght (mm)	Order code
6	SIN +	9	3000	003108015216
5	SIN -	22	5000	003108015217
12	COS +	10	10000	003108015215
11	COS -	23		
3	GND	24		
8	DATA +	1		
7	DATA -	14		
10	SHIELD	26		



SIGNAL CABLES for models TC-E 60 - 80 - 100 - 130 - 180 feedback E1 incremental encoder for C2 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
6	A	1	Lenght (mm)	Order code
5	A/	14	3000	003108015225
12	B	2	5000	003108015226
11	B/	15	10000	003108015224
8	Z	3		
7	Z/	16		
2	HU	4		
15	HU/	NC		
9	HV	17		
14	HV/	NC		
1	HW	5		
13	HW/	NC		
4	5 VDC	11		
3	GND	24		
10	SHIELD	26		




CABLES SPECIFICATIONS

Dynamic laying cable E83517 cULus AWM STYLE 20233 and E83517 – cRUus AWM STYLE 20549 certified

SIGNAL CABLES for models TC-E 60 - 80 - 100 - 130 - 180 feedback A2 20 bit absolute encoder for C2 connection

PIN motor side	FUNCTION	PIN drive side	For cable order	
6	DATA +	1	Lenght (mm)	Order code
5	DATA -	14	3000	003108015230
4	5 VDC	11	5000	003108015231
3	GND	24	10000	003108015229
10	SHIELD	26		

Signal wired cable for FLEXI-PRO with 20 bit absolute encoder



SEE IT BEFORE IT HAPPENS

CONNECTOR SPECIFICATIONS

FLYING CONNECTORS for D0 connection

Power Connector for TC-E 40-60-80 Molex 4p	order code 007117000088
Power Connector for TC-E 40-60-80 with brake Molex 6p	order code 007117000086
Signal Connector for TC-E 40-60-80 Amp 9p	order code 007117000084

FLYING CONNECTORS FOR C2 connection

Power connector pin included BSTA108NN00580236000 + 4 PIN 60.003.11 FM/2mm CRIMP.0,35-2,5 SPRING + 4 PIN 60.001.11 FM/1mm CRIMP.0,14-1 SPRING	order code 007117000472
Signal connector pin included ASTA014NN00410235000 17p/FM + 17 PIN 60.011.11 FM/1mm CRIMP.0,14-1	order code 007117000462




FLYING CONNECTORS for C3 connection


Signal Connector for TC-E 100, 130, 180 97-3106AMI20- 29S(417)(946)(M16)(A99) cable gland included	order code 005117001770
Power Connector for TC-E 100 and 130 DL31.06A.20-15S (PG16) cable gland not included	power connector order code 005117001766 cable gland order code 005603000170
Power Connector for TC-E 180 DLC31.06A.24-10S (PG21) cable gland not included	order code 005117001768 cable gland order code 005603000300

FLYING CONNECTOR DIMENSIONS


FLYING CONNECTORS for C2 connection (90° M23 turnable connectors)



FLYING CONNECTORS for C3 connection for TC-E 100-130 (90° MS connectors)




FLYING CONNECTORS for C3 connection for TC-E 180 (90° MS connectors)



FLYING CONNECTORS for C3 connection for MS connectors

Radius curvature $RD=10 \times D$ and $Rd = 10 \times d$

TC-E 100 and 130



TC-E 180

